AmerSorb P

Product Overview

AmerSorb P is highly effective at eliminating low levels of VOCs, odors, and contaminants from indoor air, providing an ideal solution for facilities seeking relief from irritating odours caused by cigarette smoke, food preparation, and vehicle exhaust.

Key Features

IAQ Filter
Effectively removes gases and odours

Durable Construction
Metal-free design ensures safer handling and long-lasting performance

Dust-Free Operation
No carbon dusting

Easy Disposal
Suitable for incineration or shredding

Specification

ASHRAE 52.2	MERV 6
Filter Depth (mm)	22, 44, 95
Media Type	Carbon
Frame Material (Standard)	Moisture Resistant Beverage Board
Frame Material (Optional)	Galvanised Steel, Aluminium, Stainless Steel
Special Size Available	Yes
Antimicrobial Available	No
Reccomended Final Resistance	250 Pa
Max Operating Temperature	51°C
Target Gas	VOC

Initial Resistance vs. Airflow

Product Information

Nominal Size Inches (W x H x D)	Actual Size mm (W x H x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
12 x 24 x 1	289 x 594 x 22	1,700	100
20 x 24 x 1	492 x 594 x 22	2,800	
24 x 24 x 1	594 x 594 x 22	3,400	
12 x 24 x 2	289 x 594 x 44	1,700	90
20 x 24 x 2	492 x 594 x 44	2,800	
24 x 24 x 2	594 x 594 x 44	3,400	
12 x 24 x 4	289 x 594 x 95	1,700	60
20 x 24 x 4	492 x 594 x 95	2,800	
24 x 24 x 4	594 x 594 x 95	3,400	